




Product Specifications / Information



Color: Light Almond

Newer Technology Power2U

NWTPWR2U15A14A

UPC Code: 811643015326

Country of Origin: China

Electrical Specificaions

Grounding: Self

Amperage: 15 Amp

Voltage: 125 Volt

NEMA: 5-15R Compliant

Pole: 2

Wire: 3

AC Description: 15A tamper resistant, 125V, NEMA 5-15R, 2P, 3W, Decora body duplex receptacle, straight blade, residential grade, self grounding, back wired, steel strap – Light Almond

DC Description: 5.2V, 2500mA (12.5W) Duplex USB charging receptacle with integrated on/off safety switch for USB power

AC Horsepower Ratings at Rated Voltage: 1/2HP

Dielectric Voltage: Withstands 2000V per UL 498

Overload Test, HP Ratings: 125V AC, 58.8A

Current Limiting: Full Rated Current

Temperature Rise: Maximum contact temperature rise 62.95° F (27.6° C);
Max terminal temperature rise 59.36° (19.8° C)

Environmental Specifications

Flamability: Rated V-2 per UL94

Operating Temperature: -40° F to 140° F

Material Specifications

Face and Body Material: Polycarbonate

Line Contacts: Brass Triple-Wipe .031 Thick

Strap Material: Zinc-Plated Steel

Color: Light Almond



Mechanical Specifications

Terminal ID: None; Wires Attached

Terminal Accomodation: None; Wires Attached

Product ID: Ratings Marked on Device

Termination: 14 Gauge Standard Wire

Compliances

NEMA: WD-1 and WD-6

ANSI: C-73

UL 498: File E339607

UL 514D: File E339607

UL 1310: File E339607

CAN/CSA C22.2 No. 223: File E339607

Patent Number US 7,997,925 B2

Warranty: 1 Year NewerTech Product Limited

Wiring Diagram

